

Technical Datasheet

Cold welding type A for PVC in sheets

ADHESIVES & WELDING

DESCRIPTION

Cold welding solution in a tube with a needle.

Specially designed for heterogeneous vinyl floorcovering sheets that have been overlapped and double cut.

Key features:

- Invisible joint.
- Easy to apply with the needle that acts as a guide.
- Quick-drying solution.

Compatible flooring:

- Heterogeneous vinyl floorings in rolls.

Main segments of application:



TECHNICAL INFORMATION

Product

Unit weight (g) 44 (20lm)


Packaging

| | |
|-----------------|----------------|
| Pieces per box | 30 tubes |
| Box size (cm) | 320 x 220 x 90 |
| Box weight (kg) | 1.32 |
| Min. order | 1 box |

INSTALLATION

- The sheets must be overlapped and double-cut.
- Fix the tape over the joint and use hand roller to ensure bonding.
- Cut tape along the seam.
- Insert the needle of the tube into the joint and press regularly. Make sure you apply enough liquid along the joint.
- Take the tape away (after approximately 10 min).
- DO NOT remove any excess of liquid, it will disappear during normal wear.
- Cold liquid welding can be carried out 24 hours after the installation of the vinyl floor covering.
- Cold welding not valid for homogeneous, LVT and linoleum floorings, and tiles format.

ARTICLE CODE

| | SAP Code | EAN Code |
|--|----------|---------------|
|  Transparent Cold Welding | 1490 002 | 3423128423433 |

CLEANING & MAINTENANCE

No cleaning or maintenance required.