

iQ One

Datasheet

Classification	Norm	Tarkett Value
Product type	EN14565 - ISO 19322	Floor coverings based upon synthetic thermoplastic polymers
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Technical Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	2800 g/m ²
Surface treatment		New iQ PUR
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #		0019-0056-DoP-2015-11
Slip resistance (EN 13893)	EN 13893	Class DS ($\mu \geq 0,30$)
Reaction to fire	EN 13501-1	Bfl-s1
Reaction to fire	EN ISO 9239-1	≥ 8 kW/m ²
Technical Performance	Norm	Tarkett Value
Curl resultant to heat	ISO 19322 - PROCEDURE A	$\leq 8 $ mm
Castor chair	ISO 4918 - EN 425	Suitable
Light fastness	ISO 105-B02 (method 3)	≥ 6
Chemical resistance	ISO 26987	Excellent Resistance
Slip resistance	DIN 51130	R9
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Total VOC Emissions (after 28 days)	EN 16516	Gold (≤ 100 $\mu\text{g} / \text{m}^3$)
Recyclability through ReStart®	ISO 14021	Offcuts / Post-use - Contact Tarkett for more information
Material Health Statement		Available
Recycled content	ISO 14021	25,5 %
French emissions label		A+
BREEAM rating		A+
EPD		Available
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		7,3 kg CO ₂ eq /m ²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		6,66 kg CO ₂ eq /m ²
Dimensions and designs		
Roll		Roll 2 x 23 m
Number of designs available		10



The above information is subject to modification for the benefit of further improvement (04/03/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.