

# iD inspiration High Traffic 70

## Datasheet

| Classification                                       | Norm  | Tarkett Value   |
|--|---|---|
| Product type   | EN ISO 10582  | Heterogeneous poly(vinyl chloride) floor coverings        |
| Domestic classification                              | EN ISO 10874  | 23 Heavy  |
| Commercial classification                            | EN ISO 10874  | 34 Very Heavy   |
| Industrial classification                            | EN ISO 10874  | 43 Heavy  |
| Commercial warranty (in years)                       |   | 10 years  |
| Residential warranty (in years)                      |   | 20 years  |
| Technical Characteristics                            | Norm  | Tarkett Value   |
| Total thickness                                      | EN ISO 24346  | 2,50 mm   |
| Wear layer thickness                                 | EN ISO 24340  | 0,70 mm   |
| Total weight   | EN ISO 23997  | 3950 g/m <sup>2</sup>                                     |
| Binder content                                       | EN ISO 10582  | Type I  |
| Surface treatment                                    |   | TEKTANIUM®  |
| Embossing in Register                                |   | Yes   |
| Bevelled edges                                       |   | No bevel<br>4 sides                                       |
| Installation method                                  |   | Glue-Down   |
| Performance for CE Marking                           | Norm  | Tarkett Value   |
| Declaration of Performance #                         | EN 14041  | 0132-0085-DoP-2020-03                                     |
| Technical Performance                                | Norm  | Tarkett Value   |
| Dimensional stability                                | EN ISO 23999  | Average measured value : ≤ 0.10 %                         |
| Curl resultant to heat                               | EN ISO 23999  | ≤  2  mm  |
| Reaction to fire                                     | EN 13501-1  | Bfl-s1  |
| Residual indentation                                 | EN ISO 24343-1  | ≤ 0,05 mm   |
| Furniture leg  | EN ISO 16581  | No damage   |
| Furniture leg  | EN ISO 16581  | No damage   |
| Castor chair   | EN ISO 4918   | No damage   |
| Impact sound reduction - ΔLw                         | EN ISO 717-2  | 3 dB  |
| Reduction of in-room impact noise                    | NF S31-074  | Class C (≤ 85 dB)   |
| Thermal resistance                                   | EN ISO 10456  | 0,02 m <sup>2</sup> ·K/W                                  |
| Light fastness                                       | EN ISO 105-B02  | ≥ 6   |
| Chemical resistance                                  | EN ISO 26987  | Excellent Resistance                                      |
| Slip resistance                                      | DIN 51130   | R9<br>R10   |
| Slip resistance (EN 13893)                           | EN 13893  | Class DS (μ ≥ 0,30)                                       |
| Static Electrical Propensity                         | EN 1815   | Antistatic (≤ 2 kV)                                       |
| Underfloor heating                                   |   | Suitable (subfloor temperature maximum 27°C)              |
| Sustainability performances                          | Norm  | Tarkett Value   |
| Recyclability through ReStart®                       |   | Offcuts / Post-use - Contact Tarkett for more information |
| Recycled content                                     | ISO 14021   | 35 %  |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) |   | 4,33 kg CO <sub>2</sub> eq /m <sup>2</sup>                |
| Total VOC Emissions (after 28 days)                  | EN 16516  | Platinum (≤ 10 μg/m <sup>3</sup> )                        |
| Dimensions and designs                               |   |   |
| Plank  | Plank 1200x200mm - 15 planks=3,6 m <sup>2</sup> /box - 55 boxes/pallet<br>Plank 1200 x 285mm - 11 planks=3,76 m <sup>2</sup> /box - 54 boxes/pallet<br>Plank 250 x 1500 mm - 10 planks=3,75 m <sup>2</sup> /box - 56 boxes/pallet   |   |
| Tile   | Tile 50 x 50 cm - 15 tiles=3,75 m <sup>2</sup> /box - 52 boxes/pallet<br>Tile 666 x 666 mm - 8 tiles=3,55 m <sup>2</sup> /box - 40 boxes/pallet<br>Tile 666 x 333mm - 16 tiles=3,55 m <sup>2</sup> /box - 40 boxes/pallet<br>Tile 500 x 1000 mm - 7 tiles=3,5 m <sup>2</sup> /box - 54 boxes/pallet |   |
| Number of designs available                          |   | 100   |

Embossing in register : on Authentics references

Slip resistance DIN : R9/R10 depending on embossing



The above information is subject to modification for the benefit of further improvement (07/04/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.